NSN 5305-01-311-7133

Thread Class:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-311-7133

| 3a |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.880 inches |
| Fastener Length: |
| Between 2.920 inches and 3.000 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.735 inches and 0.750 inches |
| Head Height: |
| Between 0.492 inches and 0.500 inches |
| Hole Diameter: |
| Between 0.061 inches and 0.067 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.500 inches |
| Width Across Flats: |
| Between 0.375 inches and 0.379 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 13 |
| Min. Tensile Strength (psi): |
| 170000 pounds per square inch |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 155000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon flats |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2, cl 3 federal specification single treatment response |
| |

NSN 5305-01-311-7133Socket Head Cap Screw - Page 2 of 2



| Inread Series Designator: |
|----------------------------|
| Unc |
| Specification Or Standard: |
| 6 type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A003b0