Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-311-8694

2a	
Thread Dire	ection:
Right-hand	
Thread Ler	ngth:
0.500 inche	-
Fastener L	ength:
0.500 inche	s
Head Style	:
Pan	
Head Diam	eter:
0.314 inche	S
Head Heigl	nt:
0.090 inche	S
Washer Qu	antity:
2	
Internal Dri	ive Style:
Slot	
Thread Dia	meter:
0.164 inche	S
Thready Q	y Per Inch (tpi):
32	
Hardness F	Rating:
40.0 rockwe	ell c fastener
Secondary	Washer Relationship To Primary Washer:
Not identica	d
Secondary	Washer Style:
Flat	
Primary Wa	asher Outside Diameter:
0.293 inche	S
Secondary	Washer Outside Diameter:
0.293 inche	s
Primary Wa	asher Style:
Split helical	ring
Primary Wa	asher Material Thickness:
0.040 inche	S
Secondary	Washer Material Thickness:
0.016 inche	S
Material:	
Stainless st	
Surface Tro	eatment:
Passivate	

NSN 5305-01-311-8694

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:

Unc

Specification Data:

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0