NSN 5305-01-312-0243

Close Tolerance Screw - Page 1 of 2

3a





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.553 inches and 0.603 inches Fastener Length: Between 1.688 inches and 1.718 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.708 inches and 0.765 inches **Grip Diameter:** Between 0.3735 inches and 0.3747 inches Internal Drive Style: High-torque **Thread Diameter:** 0.375 inches Grip Length: Between 1.115 inches and 1.135 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head **Product Name:** Navy special project **Special Features:** Dry film lubricant per mil-I-46010 Color: Red threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Phosphate

Thread Series Designator:

Unjf

24

NSN 5305-01-312-0243

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

