

View Online at <https://aerobasegroup.com/nsn/5305-01-312-0704>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.877 inches and 0.927 inches

Fastener Length:

Between 1.825 inches and 1.855 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.214 inches and 1.272 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Single Shear Strength:

108000 pounds per square inch

Internal Drive Style:

High-torque

Thread Diameter:

0.625 inches

Grip Length:

Between 0.928 inches and 0.948 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1980 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.