

View Online at <https://aerobasegroup.com/nsn/5305-01-312-2594>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.507 inches

Fastener Length:

Between 1.304 inches and 1.334 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.703 inches and 0.762 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-8844 military specification 2nd material response or ams 6414 assn standard 2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium or cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 type 1 cl 3 federal specification 1st treatment response or qq-p-416 type 1 cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1221 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.