

View Online at <https://aerobasegroup.com/nsn/5305-01-312-3898>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.110 inches and 0.200 inches

Fastener Length:

Between 0.600 inches and 0.630 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.160 inches and 0.230 inches

First Diameter From Head:

Between 0.084 inches and 0.094 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.040 inches and 0.070 inches

Point Style:

Flat

Internal Drive Style:

Slot

Thread Diameter:

0.125 inches

Thready Qty Per Inch (tpi):

40

Countersink Angle:

Between 98.0 degrees and 102.0 degrees

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347

Material Specification:

Qq-s-763 federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Beps 6.003 cagec 77068 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0