NSN 5305-01-312-5006

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-312-5006 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.208 inches and 0.258 inches **Fastener Length:** Between 0.468 inches and 0.498 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.194 inches and 0.225 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, cl2 ty2 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-01-312-5006

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0