## NSN 5305-01-312-5007

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-312-5007 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.438 inches and 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.340 inches and 0.385 inches **Head Height:** Between 0.068 inches and 0.081 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 **Screw Material Specification:** Qq-s-763 federal specification all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:**