NSN 5305-01-312-5915

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-312-5915 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.569 inches and 0.619 inches **Fastener Length:** Between 4.829 inches and 4.859 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.722 inches and 0.740 inches **Head Height:** Between 0.206 inches and 0.220 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 4.240 inches and 4.260 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-312-5915

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0