## NSN 5305-01-312-8061

Close Tolerance Screw - Page 1 of 2

3a

View Online at https://aerobasegroup.com/nsn/5305-01-312-8061

**Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.444 inches and 0.494 inches Fastener Length: Between 0.829 inches and 0.859 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.3898 inches and 0.3948 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Grip Length: Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response Surface Treatment: Aluminum **Surface Treatment Specification:** Mil-c-83488, type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 

76301-3-963 manufacturers standard

## NSN 5305-01-312-8061

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-s-6049 spec.

