

View Online at <https://aerobasegroup.com/nsn/5305-01-313-0916>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.156 inches

**Fastener Length:**

0.625 inches

**Head Style:**

Truss

**Head Diameter:**

Between 0.166 inches and 0.183 inches

**Head Height:**

Between 0.088 inches and 0.107 inches

**First Diameter From Head:**

Between 0.073 inches and 0.083 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.459 inches and 0.479 inches

**Point Style:**

Flat

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1213 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 1214 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 1330 or steel comp 1548

**Material Specification:**

Astm a108 assn standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A003b0