NSN 5305-01-313-3974

Close Tolerance Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5505-01-315-3974
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.476 inches and 0.526 inches
Fastener Length:
Between 1.674 inches and 1.704 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.429 inches and 0.479 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.312 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1581 professional/industrial association standard
Shelf Life:
N/a

Unit Of Measure:

NSN 5305-01-313-3974

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0