

View Online at <https://aerobasegroup.com/nsn/5305-01-313-3975>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.241 inches and 0.301 inches

**Fastener Length:**

Between 0.423 inches and 0.453 inches

**Head Diameter:**

Between 0.317 inches and 0.347 inches

**Head Height:**

Between 0.100 inches and 0.130 inches

**Internal Drive Style:**

Slot

**Material Accommodated Thickness:**

Between 0.094 inches and 0.125 inches

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Special Features:**

Screw has a non-floating head

**Material:**

Steel comp 304 stand-off

**Material Specification:**

Mil-s-23195 military specification single material response stand-off or qq-s-763 federal specification single material response stand-off or ams 5639 assn standard single material response stand-off or astm a493 assn standard single material response stand-off

**Surface Treatment:**

Passivate stand-off

**Surface Treatment Specification:**

Qq-p-35 type 1, or type 2, or type 3, or type 4 federal specification single treatment response stand-off

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-23195 spec.