NSN 5305-01-313-3975

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-313-3975 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.241 inches and 0.301 inches **Fastener Length:** Between 0.423 inches and 0.453 inches **Head Diameter:** Between 0.317 inches and 0.347 inches **Head Height:** Between 0.100 inches and 0.130 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.094 inches and 0.125 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Screw has a non-floating head Material: Steel comp 304 stand-off **Material Specification:** Mil-s-23195 military specification single material response stand-off or qq-s-763 federal specification single material response stand-off or ams 5639 assn standard single material response stand-off or astm a493 assn standard single material response stand-off **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 type 1, or type 2, or type 3, or type 4 federal specification single treatment response stand-off **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-s-23195 spec.

Mil-std (military Standard):

A003b0