NSN 5305-01-313-9329

Shoulder Screw - Page 1 of 2

Between 0.190 inches and 0.250 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

2a



View Online at https://aerobasegroup.com/nsn/5305-01-313-9329

Fastener Length:
Between 0.485 inches and 0.515 inches
Head Style:
Flat countersunk
Head Diameter:
0.223 inches
Shoulder Diameter:
0.141 inches first shoulder and 0.142 inches first shoulder
Shoulder Length:
0.265 inches first shoulder and 0.295 inches first shoulder
Internal Drive Style:
Slot
End Application:
Prowler ea-6b aircraft; aircraft, intruder a-6e
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
33.0 rockwell c and 37.0 rockwell c
Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Color:
Green top of head
Material:
Steel comp 4037 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unc

NSN 5305-01-313-9329

Shoulder Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0