## NSN 5305-01-313-9331

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-313-9331 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.188 inches and 0.248 inches **Fastener Length:** Between 0.563 inches and 0.593 inches **Head Style:** Flat countersunk **Head Diameter:** 0.223 inches **Shoulder Diameter:** 0.141 inches first shoulder and 0.142 inches first shoulder **Shoulder Length:** 0.305 inches first shoulder and 0.375 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Color: Black top of head Material: Steel comp 4037 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-01-313-9331

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0