

View Online at <https://aerobasegroup.com/nsn/5305-01-314-2397>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.633 inches

**Fastener Length:**

Between 1.617 inches and 1.664 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.951 inches and 1.014 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.500 inches

**Grip Length:**

1.000 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

156000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837 type 2 cl 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.