

View Online at <https://aerobasegroup.com/nsn/5305-01-314-2456>

Thread Direction:

Right-hand

Thread Length:

Between 11.7 millimeters and 14.3 millimeters

Fastener Length:

Between 13.7 millimeters and 14.3 millimeters

Head Style:

Flat countersunk

Head Diameter:

Between 7.2 millimeters and 8.0 millimeters

Internal Drive Style:

Torque set

Thread Diameter:

4.0 millimeters

Min. Tensile Strength (psi):

1100 megapascals

Thread Pitch In Millimeters:

0.7

External Thread Tolerance Class:

4h6h

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Bearing Surface Of Head Surface Finish:

0.8 micrometers

Shank Surface Finish:

0.8 micrometers

Thread Surface Finish:

0.8 micrometers

Thread Series Designator:

Mj

Specification Data:

80205-na0070 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0