Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-314-3458

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.359 inches and 0.391 inches
Fastener Length:
Between 1.047 inches and 1.078 inches
Head Style:
Knurled no. 1
Head Diameter:
Between 0.433 inches and 0.443 inches
Head Height:
Between 0.234 inches and 0.266 inches
First Diameter From Head:
Between 0.125 inches and 0.135 inches
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Special Features:
Cone point 82 deg
Material:
Material: Steel comp 303
Steel comp 303
Steel comp 303 Material Specification:
Steel comp 303 <b>Material Specification:</b> Qq-s-764 cond a federal specification single material response
Steel comp 303 <b>Material Specification:</b> Qq-s-764 cond a federal specification single material response <b>Surface Treatment:</b>
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification:
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072 finish no. E300 military specification single treatment response
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification:
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072 finish no. E300 military specification single treatment response Thread Series Designator:
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072 finish no. E300 military specification single treatment response Thread Series Designator: Unf
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072 finish no. E300 military specification single treatment response Thread Series Designator: Unf Shelf Life:
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072 finish no. E300 military specification single treatment response Thread Series Designator: Unf Shelf Life: N/a
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072 finish no. E300 military specification single treatment response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:
Steel comp 303 Material Specification: Qq-s-764 cond a federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072 finish no. E300 military specification single treatment response Thread Series Designator: Unf Shelf Life: N/a

## NSN 5305-01-314-3458

Externally Relieved Body Screw - Page 2 of 2



**Fiig:** A003b0

Mil-std (military Standard):

Mil-f-14072 spec.