

View Online at <https://aerobasegroup.com/nsn/5305-01-314-5138>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.338 inches

**Fastener Length:**

Between 0.7605 inches and 0.7905 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.294 inches and 0.332 inches

**Internal Drive Style:**

Torque-set ribbed

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Titanium alloy uns r56400

**Screw Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Shank Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1221 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0