NSN 5305-01-314-5486

Specification Data:

80205-nas1581 professional/industrial association standard

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-314-5486

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.743 inches and 0.793 inches
Fastener Length:
Between 1.941 inches and 1.971 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.690 inches and 0.761 inches
Grip Diameter:
Between 0.4990 inches and 0.4995 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.500 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5305-01-314-5486

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0