Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-314-6738

Thread C	lass:
3a	
Thread D	virection:
Right-har	nd
Thread L	ength:
0.180 inc	hes
Fastener	Length:
1.000 inc	hes
Head Sty	le:
Fillister	
Head Dia	meter:
0.270 inc	hes
Head He	ight:
0.082 inc	hes
First Dia	meter From Head:
0.105 inc	hes
Distance	From Largest Bearing Surface Of Head To End Of First Diameter:
0.820 inc	hes
Internal	Drive Style:
Slot	
Thread D	viameter:
0.138 inc	hes
Thready	Qty Per Inch (tpi):
32	
External	y Relieved Body Diameter Quantity:
1	
Material:	
Steel con	np 304
Material	Specification:
Qq-s-763	federal specification single material response
Surface	Treatment:
Passivate	
Surface	Treatment Specification:
Qq-p-35	ederal specification single treatment response
Thread S	eries Designator:
Unc	
Shelf Life	e:
N/a	
Unit Of M	leasure:
Demilita	ization:

## NSN 5305-01-314-6738

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

