## NSN 5305-01-315-3779

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-315-3779 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.325 inches **Fastener Length:** Between 0.735 inches and 0.780 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.160 inches and 0.175 inches **Head Height:** Between 0.075 inches and 0.085 inches **First Diameter From Head:** Between 0.053 inches and 0.056 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.455 inches and 0.485 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Color: Black fastener Material: Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 384 fastener **Material Specification:** Qq-s-763 federal specification 1st material response fastener or qq-s-763 federal specification 2nd material response fastener or qq-s-763 federal specification 3rd material response fastener or astm a493 assn standard 4th material response fastener **Surface Treatment:** Oxide fastener **Surface Treatment Specification:** Mil-c-13924 class 2 military specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-01-315-3779

Externally Relieved Body Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.