## NSN 5305-01-315-4191

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-315-4191 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.140 inches **Fastener Length:** 0.370 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.144 inches and 0.146 inches **Head Height:** Between 0.060 inches and 0.066 inches **First Diameter From Head:** Between 0.069 inches and 0.071 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.170 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 56 **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project **Special Features:** Undercut 0.015 wide x 0.010-0.012 deep; shoulder 0.060 in. Nom lg; 0.109 in. Nom dia Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 4 federal specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-01-315-4191

Externally Relieved Body Screw - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0