Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-315-4191

| Thread Class: |
|--------------------------------------------------------------------------------------|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.140 inches |
| Fastener Length: |
| 0.370 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.144 inches and 0.146 inches |
| Head Height: |
| Between 0.060 inches and 0.066 inches |
| First Diameter From Head: |
| Between 0.069 inches and 0.071 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.170 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.086 inches |
| Width Across Flats: |
| Between 0.078 inches and 0.079 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Product Name: |
| Navy special project |
| Special Features: |
| Undercut 0.015 wide x 0.010-0.012 deep; shoulder 0.060 in. Nom lg; 0.109 in. Nom dia |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a582 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 type 4 federal specification single treatment response |
| Thread Series Designator: |

Unc

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0