

View Online at <https://aerobasegroup.com/nsn/5305-01-315-5523>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.146 inches and 0.166 inches

Fastener Length:

Between 0.297 inches and 0.327 inches

Head Style:

Fillister

Head Diameter:

Between 0.166 inches and 0.183 inches

Head Height:

Between 0.088 inches and 0.107 inches

First Diameter From Head:

Between 0.073 inches and 0.083 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.131 inches and 0.181 inches

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1213 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 1214 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 1330 or steel comp 1548

Material Specification:

Astm a108 assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fiig:

A003b0