NSN 5305-01-315-5534

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-315-5534

Thread Class:
3a Thread Direction:
Right-hand
Thread Length:
Between 0.617 inches and 0.667 inches
Fastener Length: Between 0.752 inches and 0.782 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.510 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Features Provided:
Cetyl alcohol lubricant
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Navy special project
Special Features:
Cetyl alcohol per mil-l-87132 type 1 gr b
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Mil-c-83488 type 2 cl 3 military specification single treatment response
Thread Series Designator:
11-34

Unjf

NSN 5305-01-315-5534

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.

