

View Online at <https://aerobasegroup.com/nsn/5305-01-315-5648>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 10.6 millimeters and 12.0 millimeters

**Fastener Length:**

12.0 millimeters

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 7.7 millimeters and 8.0 millimeters

**Head Height:**

Between 2.2 millimeters and 2.4 millimeters

**Internal Drive Style:**

Torque set

**Thread Diameter:**

4.0 millimeters

**Min. Tensile Strength (psi):**

1100 megapascals

**Thread Pitch In Millimeters:**

0.7

**External Thread Tolerance Class:**

6g

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response or ams 5732 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Special Features:**

Surface texture bearing surface of head, shank and threads 0.8 max

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0068 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0