

View Online at <https://aerobasegroup.com/nsn/5305-01-315-7094>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.85 millimeters and 0.95 millimeters

**Fastener Length:**

Between 51.7 millimeters and 52.3 millimeters

**Head Style:**

Pan

**Head Diameter:**

Between 9.7 millimeters and 10.0 millimeters

**Head Height:**

Between 2.8 millimeters and 3.0 millimeters

**Grip Diameter:**

Between 4.965 millimeters and 4.990 millimeters

**Single Shear Strength:**

6600 megapascals

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

5.0 millimeters

**Grip Length:**

Between 42.8 millimeters and 43.2 millimeters

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Thread Pitch In Millimeters:**

0.8

**External Thread Tolerance Class:**

4h6h

**Surface Finish:**

0.8 micrometers threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0035 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.