## NSN 5305-01-315-7095

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-315-7095

| View Online at https://aerobasegroup.com/nsn/5305-01-315-7095  |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Fastener Length:   |
| 0.590 inches   |
| Head Style:  |
| Knurled no. 1  |
| Head Diameter:   |
| 0.531 inches   |
| Head Height:   |
| 0.530 inches   |
| Internal Drive Style:  |
| Slot   |
| Material Accommodated Thickness:   |
| Between 0.155 inches and 0.217 inches  |
| Thread Diameter:   |
| 0.250 inches   |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Min. Tensile Strength (psi):   |
| 140000 pounds per square inch  |
| Material:  |
| Steel comp 304 stand-off   |
| Material Specification:  |
| Qq-s-763 federal specification single material response stand-off  |
| Surface Treatment:   |
| Passivate  |
| Special Test Features:   |
| Special quality control testing  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Test Data Document:  |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5305-01-315-7095

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.