## NSN 5305-01-315-7398

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-315-7398 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.500 inches **Fastener Length:** Between 1.565 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c fastener and 45.0 rockwell c fastener Minimum Yield Strength: 155000 pounds per square inch **Product Name:** Navy special project Material: Steel fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response fastener **Thread Series Designator:** Unrc

**Specification Data:** 

80205-nas1352 professional/industrial association standard

## NSN 5305-01-315-7398

Socket Head Cap Screw - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0