

View Online at <https://aerobasegroup.com/nsn/5305-01-315-9067>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.322 inches and 0.384 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.340 inches and 0.385 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

60000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1120 or steel comp 1132

Screw Material Specification:

Astm-a29 assn standard all material responses

Screw Surface Treatment:

Zinc and chromate

Screw Surface Treatment Specification:

Astm b633 type 2 assn standard single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

1 type and 2s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0