NSN 5305-01-315-9510

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-315-9510 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.480 inches and 0.520 inches **Fastener Length:** 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** 0.375 inches **Head Height:** 0.250 inches **First Diameter From Head:** Between 0.190 inches and 0.210 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.000 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 1, type 2; type 3 or type 4 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-315-9510

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0