NSN 5305-01-316-2919

Thread Class:

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-316-2919



За **Thread Direction:** Right-hand Thread Length: Between 0.454 inches and 0.521 inches **Fastener Length:** Between 1.902 inches and 1.949 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.634 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.428 inches and 1.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:**

Nas 672 assn standard single treatment response or mil-c-8837 type 2, cl 2 military specification single treatment response

Unjf

Shelf Life:

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Thread Series Designator:

Ams 6487 assn standard single material response

N/a

NSN 5305-01-316-2919

Close Tolerance Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.