NSN 5305-01-316-3171

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-316-3171 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** Between 0.9155 inches and 0.9855 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.294 inches and 0.332 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Titanium alloy uns r56400 **Screw Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1221 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-316-3171Machine Screw - Page 2 of 2



Fiig:

A500d0