NSN 5305-01-316-5469

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-316-5469

| Thread Class |
|----------------------------------------------------------------------------------------------------------|
| Thread Class: |
| Za Thread Direction. |
| Thread Direction: |
| Right-hand |
| Thread Length: 1.770 inches |
| |
| Fastener Length: 10.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.818 inches and 0.828 inches |
| Head Height: |
| 0.690 inches |
| Hole Diameter: |
| Between 0.093 inches and 0.098 inches |
| |
| Internal Drive Style: Slot |
| Thread Diameter: |
| 0.500 inches |
| |
| Hole Quantity: 2 |
| Thready Qty Per Inch (tpi): |
| 13 |
| |
| Min. Tensile Strength (psi): 260000 pounds per square inch |
| Screw Material: |
| Cobalt comp mp-35-n or steel comp xm-13 |
| Screw Material Specification: |
| Ams 5844 assn standard 1st material response or ams 5629, cond h1050 assn standard 2nd material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Special Features: |
| |
| 177000 psi min. Tensile strength on alternate material ams 5629 Thread Series Designator: |
| Thread Series Designator: |
| Unc Shelf Life: |
| N/a |

NSN 5305-01-316-5469

Machine Screw - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A500d0