Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-317-0078

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 2.389 inches |
| Fastener Length: |
| 2.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.419 inches and 0.438 inches |
| Head Height: |
| Between 0.209 inches and 0.219 inches |
| Hole Diameter: |
| Between 0.044 inches and 0.050 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| 0.156 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 45.0 rockwell c |
| Hole Configuration Style: |
| Hexagon flats |
| Material: |
| Steel |
| Surface Treatment: |
| Zinc and chromate |
| Surface Treatment Specification: |
| Astm b633 type 2, cl fe/zm 5 assn standard single treatment response |
| Thread Series Designator: |
| |

Unc

NSN 5305-01-317-0078

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

