NSN 5305-01-317-1510

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-317-1510 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.376 inches and 0.451 inches **Fastener Length:** Between 1.766 inches and 1.811 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.287 inches and 0.334 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas517 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A500d0