NSN 5305-01-317-1782

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-317-1782

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.875 inches
Fastener Length:
6.875 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.977 inches and 1.000 inches
Head Height:
Between 0.492 inches and 0.500 inches
Shoulder Diameter:
0.746 inches first shoulder and 0.748 inches first shoulder
Shoulder Length:
6.000 inches first shoulder
Hole Diameter:
0.062 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
0.500 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
11
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Round
Shoulder Shape:
Round first shoulder
Material:
Steel
Surface Treatment:
Zinc and chromate

NSN 5305-01-317-1782

Shoulder Screw - Page 2 of 2



Surface Treatment Specification:

Astm b633 type 2 cl 3 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0