NSN 5305-01-317-3403

Thread Class:

Right-hand

Thread Direction:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-317-3403

Thread Length:
Between 0.658 inches and 0.750 inches
Fastener Length:
Between 0.720 inches and 0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.313 inches
Head Height:
Between 0.185 inches and 0.190 inches
Internal Drive Style:
Hexagon
End Application:
5820-01-278-5201, amplifier radio
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Purchase Description Identification:
80063-a3100913-001

NSN 5305-01-317-3403

Socket Head Cap Screw - Page 2 of 2



6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0