

View Online at <https://aerobasegroup.com/nsn/5305-01-317-3994>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.213 inches and 0.233 inches

Fastener Length:

Between 1.285 inches and 1.305 inches

Head Style:

Hexagon

Head Height:

Between 0.083 inches and 0.103 inches

Width Between Flats:

Between 0.365 inches and 0.385 inches

First Diameter From Head:

Between 0.161 inches and 0.181 inches

Second Diameter From Head:

Between 0.1966 inches and 0.1969 inches

Third Diameter From Head:

Between 0.083 inches and 0.093 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.021 inches and 0.041 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.005 inches and 1.010 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 1.062 inches and 1.082 inches

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

36.0 rockwell c and 42.0 rockwell c

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 630 or steel comp 324

Material Specification:

Qq-s-763, cond a federal specification 2nd material response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0