NSN 5305-01-317-3995

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-317-3995 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.943 inches and 0.963 inches **Fastener Length:** Between 1.005 inches and 1.025 inches **Head Style:** Hexagon **Head Height:** Between 0.053 inches and 0.063 inches Width Between Flats: Between 0.302 inches and 0.322 inches **First Diameter From Head:** Between 0.146 inches and 0.166 inches **Second Diameter From Head:** Between 0.1877 inches and 0.1879 inches Third Diameter From Head: Between 0.089 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.021 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.729 inches and 0.734 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.786 inches and 0.806 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Thread Series Designator:** Unc

N/a

Shelf Life:

NSN 5305-01-317-3995

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0