NSN 5305-01-317-4013



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-317-4013 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.198 inches **Fastener Length:** Between 0.690 inches and 0.710 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.071 inches and 0.091 inches **Shoulder Diameter:** 0.2490 inches second shoulder and 0.2492 inches second shoulder **Shoulder Length:** 0.378 inches second shoulder and 0.398 inches second shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 36.0 rockwell c and 42.0 rockwell c **Shoulder Shape:** Round second shoulder **Special Features:** 0.148 in. Min through 0.158 in. Maximum dia. By 0.052 in. Min through 0.072 in. Maximum length undercut beneath second shoulder; finish coat all surfaces with solid film lubricant per mil-I-46010 Material:

Steel comp 630

Material Specification:

Aisi assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 1, 2 or 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

NSN 5305-01-317-4013

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0