

View Online at <https://aerobasegroup.com/nsn/5305-01-317-5216>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.720 inches and 0.750 inches

**Fastener Length:**

Between 3.215 inches and 3.255 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.853 inches and 0.875 inches

**Head Height:**

Between 0.365 inches and 0.375 inches

**Shoulder Diameter:**

0.621 inches first shoulder and 0.623 inches first shoulder

**Shoulder Length:**

2.495 inches first shoulder and 2.505 inches first shoulder

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.500 inches

**Width Across Flats:**

0.312 inches

**Thready Qty Per Inch (tpi):**

13

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 43.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4340 or steel comp e4340

**Material Specification:**

Ams 6415 assn standard 1st material response or mil-s-5000 military specification 2nd material response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.