NSN 5305-01-317-5218

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-317-5218 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.385 inches **Fastener Length:** Between 1.365 inches and 1.385 inches **Head Style:** Hexagon **Head Height:** Between 0.115 inches and 0.135 inches Width Between Flats: Between 0.427 inches and 0.447 inches **Shoulder Diameter:** 0.245 inches first shoulder and 0.250 inches first shoulder **Shoulder Length:** 0.990 inches first shoulder and 1.010 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Special Features:** Finish coat all surface with drying type preservative oil Material: Steel comp 1020 **Surface Treatment: Passivate Surface Treatment Specification:** Dod-p-16232, ty m cl 1 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-317-5218

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

spec.