NSN 5305-01-317-8157

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-317-8157 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.198 inches **Fastener Length:** Between 0.755 inches and 0.775 inches **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.060 inches and 0.080 inches **Shoulder Diameter:** 0.2490 inches second shoulder and 0.2492 inches second shoulder **Shoulder Length:** 0.443 inches second shoulder and 0.463 inches second shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 36.0 rockwell c and 42.0 rockwell c **Shoulder Shape:** Round all shoulders **Special Features:** Undercut threads length 0.062in., diameter 0.158in. Material: Steel comp 630 **Material Specification:** Aisi 630 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-317-8157

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0