

View Online at <https://aerobasegroup.com/nsn/5305-01-317-8190>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.128 inches and 0.162 inches

**Fastener Length:**

0.188 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.105 inches and 0.119 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.060 inches

**Thready Qty Per Inch (tpi):**

80

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 430 or steel comp 302 or steel comp 303 or steel comp 303se

**Screw Material Specification:**

Qq-s-763 federal specification 1st material response or mil-s-7720 military specification 2nd material response or astm a582 assn standard 3rd material response or astm a582 assn standard 4th material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

3 type and 2c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-7720 spec.