NSN 5305-01-317-9017

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-317-9017

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.607 inches and 1.750 inches
Fastener Length:
1.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.642 inches and 0.656 inches
Head Height:
Between 0.430 inches and 0.438 inches
Locking Feature:
Patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.438 inches
Width Across Flats:
0.375 inches
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener
Material Specification:
Astm a493 assn standard all material responses fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unc
Shalf Life:

N/a

NSN 5305-01-317-9017

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0