

View Online at <https://aerobasegroup.com/nsn/5305-01-318-4692>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.800 inches and 2.000 inches

**Fastener Length:**

2.000 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.107 inches and 1.125 inches

**Head Height:**

Between 0.740 inches and 0.750 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.750 inches

**Width Across Flats:**

0.625 inches

**Thready Qty Per Inch (tpi):**

10

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

37.0 rockwell c fastener and 45.0 rockwell c fastener

**Minimum Yield Strength:**

150000 pounds per square inch

**Material:**

Steel uns k03104 fastener

**Material Specification:**

Astm a594 assn standard single material response fastener

**Surface Treatment:**

Zinc fastener and chromate fastener

**Surface Treatment Specification:**

Astm b633 type 2 assn standard single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0