## NSN 5305-01-318-6163

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-318-6163 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.387 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.594 inches and 0.615 inches **Head Height:** Between 0.203 inches and 0.218 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-200/3 federal specification single material response or qq-a-225/6 assn standard single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 type 1 military specification single treatment response or mil-a-8625 type 2, cl 1 military specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A500d0

## NSN 5305-01-318-6163

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.